



Professional TV and Commercial Display Key Solution Provider

# Floor Standing Outdoor Display

Available Size: 32" 43" 55" 65" 75" 86" 98"

Kontech Floor Standing Outdoor Display is designed for advertising in outdoor conditions. With IP65 rating, it's possible to absolutely resist water and dust. The brightness of our product can reach 3000nits, about 10 times brighter than a standard LCD panel, combined with 4K resolution, which can offer a best visual enjoyment in outdoor conditions. In order to best adapt outdoor condition, our product can automatically adjust temperature and brightness. In addition, tempered glass, AG glass, touch screen, OS and so on, all of these are optional. You can choose the best functions you need. This Floor Standing Outdoor Display can be widely used in airport, park, business street, bus station etc.

Sunlight Readable	Remotely control	Fans-auto adjustable	Waterproof and dustproof	Touch Screen	Android and Windows
7*16h	Brightness auto adjustable	Anti-vandalism and Anti-corrosion	AG glass	Marketing mainstream I/O ports available	

With Light-Sensor, the brightness can automatically adjust according to the environment brightness.

Considering the conditions of outdoor, our outdoor display can reach IP65 rating, which can absolutely resist water and dust.

This outdoor display support to constantly display for 7\*16h, which can meet the needs of commercial advertising display.

**Fans-auto adjustable**

The operating temperature is about -20°C-55°C (-40°C optional). Equipped with fan-auto-adjustable system, which allows you to use in all weather.

**Remotely control**

Built-in professional advertising software, it enables you to change or release the information via PC or Mobile phone remotely. In addition, various poster models are available so that you can easily design the advertising posters.

**Anti-vandalism and Anti-corrosion**

Whether outdoor device can be used in outdoor conditions, beside to resist water and dust, anti-vandalism and anti-corrosion is the other two problems that we should take into consideration. Tempered glass and professional outdoor powder can effectively solve it.

**Sunlight Readable**

Brightness: 2000-3000nits  
Resolution: 1920\*1080 or 3840\*2160  
The brightness of outdoor display can reach 3000nits. Even place it in the case of direct sunlight, the screen will never be black. With 4K resolution, it can provide you with a best visual enjoyment.

More Functions: Timing function, Miracast, NFC, Face recognition etc.

AG glass  
Effectively prevent glare

Interactive Marketing  
To increase the interaction of our product, it is available for you to choose a touch screen.

Android and Windows  
More choices, more satisfaction

Marketing mainstream I/O ports available  
USB, HDMI, RJ45, SD Card etc.

<b>Kontech®</b> The Professional Difference		<b>KONTECH SPEC</b> 55 inch Specifications for reference
Brand	Kontech	
Product	Floor Standing Outdoor Display	
Picture		
Market	Global market	
Model Name	SW55L20	
LCD Panel	Display size	55 inch
	Active Area(mm)	1209.6*680.4mm
	Brightness(Typical)	2000nits
	Contrast(Typical)	5000:1
	Resolution (H x V)	1920*1080
	Aspect Ratio	16:9
	Response Time(Typical)	6ms
	View Angles	178°/178°
	IP Rating	IP65
	Tempered glass	YES
Backlight rated hours	50000h	
<b>Dimention</b>		
Dimention(mm)	2050mm*880mm*230mm ( Without Base ) 2100mm*999mm*400mm ( With Base )	
Packing Dimension (L*W*H)mm	TBD	
N.W	170KG	
G.W	TBD	
<b>Hardware solution</b>		
CPU	RK3288	
GPU	ARM Mali-T764	
RAM	2G	
ROM/Storage	8G/16G	
OS	Android	
Wifi	YES	
Miracast	Optional	
<b>I/O ports</b>		
USB	YES x 2	
HDMI input	YES x 1	
HDMI output	YES x 1	
RJ45	YES x 1	
SD card	YES x 1	
<b>Supporting format</b>		
Video	AVI, rm, rmvb, MKV, WMV, MOV, MP4, DAT, VOB, PMP, MPEG, MPG, FLV, ASF, TS, TP, 3GP, MPG	
Audio	MP3,WMA,MP2,OGG,AAC,M4A,MA4,FLAC, APE,3GP,WAV	
Picture	JPG、JPEG、BMP、PNG、GIF	
Dolby	Optional	
<b>Features</b>		
OSD languages	Optional	
External control	Keyboard, Mouse, PC/Mobile phone	
Bluetooth module	Optional	
Camara	Optional	
3G/4G module	Optional	
Audio output power	2*8W	
Touch screen	Optional	
Multi-screen	Optional	
AC Power Range	AC 110V~220V	
Operating Temperature	- 10°C ~ 50°C	
Accessory	Power Cable	YES
	Remote control	YES
	Battery	YES
	Warranty card	YES
	User Manual	YES
Carton Box	TBD	
Others	TBD	
Certification	TBD	